

Polyester fleece

Triflex Special Fleece



Product information

Applications

Triflex Special Fleece is used for reinforcement and layer thickness control with Triflex PMMA and PUR systems.

Properties

Triflex Special Fleece is a polyester fleece with material-reinforcing and crack-bridging properties. The mass per unit area is 110 g/m².

- Registered design

Pack size

Roll

15.00 cm x 50 m	w x l	Triflex Special Fleece
20.00 cm x 50 m	w x l	Triflex Special Fleece
26.25 cm x 50 m	w x l	Triflex Special Fleece
35.00 cm x 50 m	w x l	Triflex Special Fleece
52.50 cm x 50 m	w x l	Triflex Special Fleece
70.00 cm x 50 m	w x l	Triflex Special Fleece
105.00 cm x 50 m	w x l	Triflex Special Fleece

Moulded components

Outside corner 16 x 8 x 16 cm	w x h x d	Triflex Special Fleece
Inside corner 15 x 8 x 15 cm	w x h x d	Triflex Special Fleece

Pipe collars (2-part)

400 x 400 x 60 mm	w x l x h	Triflex Special Fleece
-------------------	-----------	------------------------

Pipe Ø 80 mm (approx. DN 70)
Pipe Ø 110 mm (approx. DN 100)
Pipe Ø 135 mm (approx. DN 125)

Colours

White

Storage

Store Triflex Special Fleece in a dry place and protect against moisture and dampness.



Instructions for use

It is used with Triflex PMMA and PUR systems. The fleece is embedded and saturated in the resin and pressed down to remove all creases and voids. The fleece is fully saturated wet-on-wet; see also the Triflex system descriptions. Fleece strips and lengths must overlap at least 5 cm at the transitions. The Triflex lettering on the fleece indicates the overlap.

General notes

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for its respective purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.